

Datasheet for

Benoslip NO

Description:

Benoslip NO is a vegetable oil-based release agent. Benoslip NO is the ideal release agent, when there are made the highest technical demands, such as precast production.

Benoslip NO is a cold resistant chemical release agent, which causes no discolouration of the concrete.

Usage:

Benoslip NO can be used as a release agent in precast production, concrete pipes etc., as well as casting on construction sites, wet casting.

Can be used on all types of moulds, such as steel/metallic, wood and plastic.

It can be universally applied and is especially well-suited where the demands for both concrete surface and maintaining moulding equipment are high.

Advantages:

Benoslip NO is vegetable oil based.

Benoslip NO causes no discolorations in the concrete.

Benoslip NO leaves a smooth surface.

Benoslip NO causes least possible capilars in the concrete.

Dosage:

Benoslip NO should be applied with spraying equipment. The best result is achieved by applying a thin uniform layer.

Potential surplus Benoslip NO is wiped off with a cloth.

Bear in mind that overdosage causes a reduction of release ability.

The range is 40 – 70 g/m², though depending on the mould's absorption and method of appliance.

Limitations:

May not be mixed with other products.

Physical properties:

Appearance :	clear liquid
Odour :	weak
pH :	non-relevant
Boiling point:	-
Flash point :	>70°C
Density :	0,845 g/ml
Water dissol. :	non dissolvable